

CENTER 300/301/302/303 Thermometer

This series of thermal couple thermometers are micro controller based testers. With very intuitive interface, the user can fully operate the tester without second thought. Some of the units (302 303) are digitally calibrated for long time stability. The whole series are equipped with RS232 interface for advance applications.



FEATURES:

- Timer Function (300, 302)
- Dual Input (301, 303)
- Dual Display (301, 303)
- RS232 interface
- Auto Power OFF
- Resolution 0.1°C, 0.1°F

SPECIFICATIONS

Range	K type: -200 ~ 1370°C; -200 ~ 2498°F (300 ~ 303) J type: -200 ~ 760°C; -200 ~ 1400°F (302, 303)
Accuracy	±0.1%+0.7°C, ±0.1%+1.4°F
Resolution	0.1°C; 0.1°F
Operation Temp	0°C ~ 50°C (< 80%RH)
Storage Temp	-20°C ~ 60°C (< 70%RH)
Battery	9V battery
Dimensions	184x64x30 mm
Weight	Approx.210g

STANDARD ACCESSORIES

Model	Battery	Operation Manual	Carrying Case	K Type bead sensor	RS-232 cable	Software
CENTER300	●	●	●	TP-K01 X 1PC	Option	Option
CENTER301	●	●	●	TP-K01 X 2PCS		
CENTER302	●	●	●	TP-K01 X 1PC		
CENTER303	●	●	●	TP-K01 X 2PCS		



300/301 K TYPE

302/303 K.J TYPE



Supplied in Australia by Instrument Choice
Call our scientists on 1300 737 871
www.instrumentchoice.com.au