

MX-KIT030

Mini XT Wellness

CO₂ - PM_{2.5} - LVOC - Temperature - Humidity - Air Pressure

Our most popular station. It monitors air renewal, fine particles and irritating VOCs to take into account the most dangerous VOCs generated indoors (formaldehyde, acetaldehyde, acrolein).

| CO ₂ /CONFINEMENT | |
|---|--|
| Detection method | Non Dispersive Infrared spectrometry (NDIR) |
| Measuring range | 0 to 5000 ppm |
| Resolution | 1 ppm |
| Accuracy | ± 50 ppm ± 3% of reading value |
| Response time 90% | < 30 seconds |
| FINE PARTICLES | |
| Detection method | Laser-based light scattering allowing PM 1/2.5 measurement and PM 4/10 estimation |
| Sampling method | Active |
| Measuring range | 0 - 1000 µg/m ³ |
| Resolution | 1 µg/m ³ |
| Accuracy | 10 µg/m ³ (<100µg/m ³) or ± 10% of reading value (>100µg/m ³) |
| Particle detection range | 0.3 µm - 10 µm |
| Sensor lifetime | > 8 years under typical conditions of use (schools, offices...) |
| LVOC (Light Volatile Organic Compounds) | |
| Detection method | Electrochemical |
| Measuring range | 30 ppb to 5 ppm |
| Resolution | 1 ppb |
| Accuracy | ±40 ppb |
| Response time 90% | < 30 seconds |
| Definition | Compounds containing up to 4 carbon atoms (aldehydes, alcohols, etc.) |
| TEMPERATURE | |
| Type of sensor | CMOS |
| Measuring range | -55°C to +125°C |
| Resolution | 0.08°C |
| Accuracy | ± 2°C between -25°C and 100°C (±0.5°C after calibration) |
| HUMIDITY | |
| Type of sensor | Capacitive |
| Measuring range | 0 to 95% |
| Resolution | 0.08% |
| Accuracy | ± 3% between 11% and 89% (± 7% for the rest of the range) |
| AIR PRESSURE | |
| Type of sensor | CMOS |
| Measuring range | 260 to 1260 hPa |
| Resolution | ± 0.02 hPa |
| Accuracy | ± 2 hPa |
| GENERAL SPECIFICATIONS | |
| Sampling interval | 10 minutes by default (customisable) |
| Conditions of use | Temperature between 0°C and +30°C. Humidity between 30 and 70 % |
| Approx. dimensions (LxIxh) / Total weight | 190x135x70 mm / 500 grams |
| Power supply and autonomy | Plug-in power supply Optional : - back-up option: 1 x 5000 mA back-up battery in case of power cut - terminal block: low voltage power supply (DC 12V/24V - 300mA max) |
| Display | Flashing LED indicators, 3 colours on configurable CO2 thresholds + operating mode indication Real-time, wireless data transfer: - Via Bluetooth, or mobile application NEMo View (iOS / Android) - NEMo Cloud services via LoRaWAN or LTE Cat-M1 network |
| Data communication | Optional: - Data downloading from device's internal memory from USB port - Modbus RS485 |
| System requirements | Operating system: Windows 7 or higher, Mac OS 10.9 or higher |
| Warranty | 2 years excluding consumables |
| Maintenance | Annual field calibration with application calibrator (VOC) Change VOC sensor every two years |
| Contents | 1 wall-mounted station 1 5V power supply 1 user guide 1 NEMo Cloud User Manual |