



★ **Detection of**  
**R32/R22/R134a**  
**R1234yf/R404A**  
**R407C/R410A**  
**R290/R502**  
**R600A .....**

## FEATURE

Air Sucking System for faster response and higher sensitivity.

Refrigerant Leakage Detector is the perfect tool for maintaining the air-condition or a cooling system with compressor and Refrigerant.

This unit used newly developed semi-conductor sensor which is extremely sensitive to variety of general used Refrigerant. Microprocessor Control with advanced digital signal processing.



## SPECIFICATIONS

- Heated Semiconductor Gas Sensor.
- 3 Level Sensitivity.
- 7 LED Tri-colored Leak Level Indicator.
- Variable Intensity Audible Alarm.
- Ambient Concentration Reset.
- 15.5"(40CM) Flexible Probe.
- Detection of R22, R32, R290, R-134a, R-404A, R-410A, R-407C, R-502, R-600A, R1234yf .....
- Refrigerants Gas.
- Sensitivity: 3g/year
- Accordance With SAE J1627, CE Design.
- Low Battery Indication.
- Battery Life: Approximately 12 hours normal use (alkaline battery).
- Reference Leak Source Included.
- Hard Carrying Case Included.
- Warm-up Time: 45 Seconds.
- Operating Temperature: 0 to 40°C(32 to 104°F)
- Dimensions: L22.1 x W7.4 x H4.7 cm
- Weight: 421g (with batteries)
- Power Source: 4 AA Size Alkaline Batteries.



\*The specifications and other information in this catalogue are subject to change without prior notice.

**CENTER**<sup>®</sup>  
**CENTER TECHNOLOGY CORP.**

4F, No.415, Jung-Jeng Road, Shu-Lin Dist., New Taipei City 238, Taiwan  
TEL: 886-2-26763926 E-Mail: center@centertek.com  
FAX: 886-2-26763925 http: //www.centertek.com

Distributed by: