

## Mi405/Mi407/Mi408/Mi412 Ammonia, Iron & Phosphate Photometers

These user-friendly Colorimeters will give you direct readings in mg/L.

Ammonia detection in water treatment systems is particularly important for aquarium owners and fish farm operators. Ammonia is highly soluble in water and extremely toxic to fish. Fish farm owners must monitor and maintain careful control of ammonia levels to ensure optimum water conditions for their stock. Milwaukee offers 2 instruments for low and medium concentrations: **Mi405** with a range of 0.00 to 9.99 mg/L and **Mi407** from 0.00 to 3.00 mg/L.

Iron is naturally present in water supplies and its presence in both potable and industrial applications is regarded as objectionable. Milwaukee offers **Mi408** Iron meter with a range of 0.00 to 5.00 mg/L.

Phosphates are present in natural waters and at concentrations typically found, do not pose any specific health threats to humans. However, excessive contamination of water courses from agricultural fertilizer run off or wastewater/effluent discharge can promote excessive algae or plant growth. Milwaukee offers **Mi412** with range 0.00 to 2.50 mg/L.



CE



### Specifications

				
	<b>Mi405 Ammonia MR</b>	<b>Mi407 Ammonia LR</b>	<b>Mi408 Iron HR</b>	<b>Mi412 Phosphate LR</b>
Range	Ammonia Iron Phosphate 0.00 to 9.99 mg/L (NH <sub>3</sub> -N)	0.00 to 3.00 mg/L (NH <sub>3</sub> -N)	0.00 to 5.00 mg/L Fe	0.00 to 2.50 mg/L PO <sub>4</sub>
Resolution	Ammonia Iron Phosphate 0.01 mg/L	0.01 mg/L	0.01 mg/L	0.01 mg/L
Accuracy	Ammonia Iron Phosphate ±0.10 mg/L @5.00 mg/L	±0.04 mg/L @1.50 mg/L	±0.03 mg/L @1.50 mg/L	±0.04 mg/L @1.00 mg/L
Method	adaptation of Nessler method	adaptation of Nessler method	adaptation of the USEPA method 315 B and Standard method 3500 - Fe B	adaptation of Ascorbic Acid method
Light Source	Blue LED 466 nm	Blue LED 466 nm	tungsten lamp	tungsten lamp
Light Detector	silicon photocell and 466 nm narrow band interference filter	silicon photocell and 466 nm narrow band interference filter	silicon photocell and 525 nm narrow band interference filter	silicon photocell and 610 nm narrow band interference filter
Environment	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%	0 to 50°C / 32 to 122°F; max RH 100%
Battery Type	1 x 9 volt	1 x 9 volt	1 x 9 volt	1 x 9 volt
Auto-off	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use	after 10 minutes of non-use
Dimensions	192 x 104 x 52 mm	192 x 104 x 52 mm	192 x 104 x 52 mm	192 x 104 x 52 mm
Weight	380 g	380 g	380 g	380 g

### Accessories

**Mi505-100** Ammonia MR reagent (100 tests)  
**Mi507-100** Ammonia LR reagent (100 tests)  
**Mi508-100** Iron HR reagent (100 tests)  
**Mi512-100** Phosphate LR reagent (100 tests)

**Mi0001** Glass cuvettes (2 pcs)  
**Mi0002** Caps for cuvettes (2 pcs)  
**Mi0003** Stoppers for cuvettes (2 pcs)  
**Mi0004** Tissue for wiping cuvettes (4 pcs)  
**Mi0005** 9V battery (1 pc)



### Ordering Information

**Mi405, Mi407, Mi408** and **Mi412** are supplied complete with 2 cuvettes, reagents for 100 tests, hard carrying case, wiping tissue, 9V battery and instructions.

Supplied in Australia by Instrument Choice  
 Call our scientists on 1300 737 871  
[www.instrumentchoice.com.au](http://www.instrumentchoice.com.au)