

OCTPROCESS

8 CHANNEL CURRENT DATA LOGGER



Features

- 16-bit readings provide high resolution
- User-defined engineering units
- Programmable start time and recording interval
- Low cost
- Real-time operation
- Reusable
- Compact
- User-friendly

Applications

- 4 to 20 mA recording
- pH recording
- Low level signal monitoring
- Photovoltaic studies
- Battery studies
- Biological sensor monitoring
- Factory process control
- Research and development
- Medical and Pharmaceutical
- Environmental studies

The OctProcess is an eight channel, battery powered, stand alone current recorder. This is an all-in-one compact, portable, easy to use device that will measure and record up to 16,383 readings per channel. The storage medium is non-volatile solid state memory, providing maximum data security even if the battery becomes discharged. The device can be started and stopped directly from your computer and its small size allows it to fit almost anywhere. The OctProcess makes data retrieval quick and easy. Simply plug it into an empty COM or USB port and our user-friendly software does the rest.



OctProcess data recorder

displays eight channels of current in an easy to use graph.

MadgeTech's Data Recorder Software is an easy to use Windows®-based software package that allows the user to effortlessly collect, display and analyze data. A variety of powerful tools allow you to examine, export, and print professional looking data with just a click of the mouse.

For more information about MadgeTech Recorders or to demo our software, visit us online at:
www.madgetech.com

OCTPROCESS SPECIFICATIONS*

Nominal Range:	±1mA	±25mA	±100mA
Measurement Range:	±1.5mA	±30mA	±120mA
+/- Input Voltage Range:	0 to 2.5V	0 to 2.5V	0 to 2.5V
Resolution:	0.05µA	1µA	5µA
Calibrated Accuracy:	±0.5%FSR	±0.1%FSR	±0.1%FSR
Input Impedance:	50Ω	10Ω	2Ω
Overload Protection:	±20mA	±100mA	±125mA
Specified Accuracy Range:	Nominal range @ 25°C		
Input Connection:	8, 3-input removable screw terminals		
Analog Conversion Time:	133 ms		
Frequency Rejection:	60 Hz		
Temperature Coefficient:	< 100ppm/°C; < 50ppm/°C typical		
Engineering Units:	User may define units up to 10 characters in length. This value is stored within the device.		
Scale Factor:	User may program any desired scaling factor from ±1.000E-31 to ±9.999E+31. The scaling factor is stored within the device.		
Start Modes:	Software programmable immediate start and delay start up to six months in advance		

Supplied in Australia by Instrument Choice
Call our scientists on 1300 737 871
www.instrumentchoice.com.au

SOFTWARE FEATURES

Multiple Graphs:	Simultaneously analyze data from several units or deployments; easily switch to a single data series	Statistics:	Calculate averages, min, max, standard deviation, and mean kinetic temperature with the touch of a button
Graphical Cursor:	One click displays readings by time, value, parameter or sample number	Export Data:	Export data in a variety of common formats, or switch to Excel® with a single click
Data Table:	Instantly access tabular view for detailed dates, times, values, and annotations	Calibration:	Automatically calculate and store calibration parameters
Scaling Options:	Autoscale function fits data to the screen, or allows user to manually enter their own values	Logger Configuration:	Easy set up and launch of data loggers with immediate or delayed start, preferred sample rate, and device ID
Formatting Options:	Change colors, line styles, plotting options, show or hide channels quickly	Communications:	Automatically sets up communications port, or lets user select configuration

*SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.
SPECIFIC WARRANTY AND REMEDY LIMITATIONS APPLY.
CALL 1-603-456-2011 OR GO TO WWW.MADGETECH.COM FOR DETAILS.

ORDERING INFORMATION

Model	Description	
OCTPROCESS-1mA	±1mA 8-Channel Current Recorder	
OCTPROCESS-25mA	±25mA 8-Channel Current Recorder	
OCTPROCESS-100mA	±100mA 8-Channel Current Recorder	
IFC110	Software, manual and RS232 interface cable	
IFC200	Software, manual and USB interface cable	
U9VL-J	Replacement battery for OctProcess	

ASK ABOUT OUR OTHER DATA RECORDERS

Temperature	Pulse/Event/State
Humidity	Low Level Current
Pressure	Low Level Voltage
pH	RF Transmitters
Level	Intrinsically Safe
Shock	Spectral Vibration
LCD Display	

For quantity discounts call 1300 737 871 or email customer-service@instrumentchoice.com.au



DOC-1051009-00 REV F 2010.08.27