

# GRAPHTEC

Isolated/Universal Input, Standalone Multi-Channel Datalogger

## midi LOGGER

GL840-M / GL840-WV / GL240



Setting New Heights  
in Data Recording

- Flexible input system for wide array of applications
- Extended memory capacity using SD memory card
- Maximum sampling interval of up to 10ms



**NEW** Multi-Input Model  
midi LOGGER GL840-M



**NEW** High Voltage  
Withstand Model  
midi LOGGER GL840-WV



**NEW** 10-Channel  
Portable Model  
midi LOGGER GL240



[www.graphteccorp.com](http://www.graphteccorp.com)

# midi LOGGER

## GL840 series & GL240



GL840 series



GL240

## Setting New Industry Standards for It's Class

### Accommodates a wide variety of measurements

#### Multifunction analog input ports

Contains a highly isolated input mechanism which ensures that signals are not corrupted by noise from other channels. The GL840/240's inputs are suitable for combined measurements from voltage, temperature, humidity, logic, and pulse signals.

#### 4 channels of Logic/Pulse inputs

Supports 4-channel logic or pulse signal inputs. Pulse mode allows cumulative, instant, or rotational values for industrial measurement capability with speed and flow.

**Voltage** Ranges from 20mV to 100V

**Temp.** Thermocouple type: R, S, B, K, E, T, J, N, W  
RTD types (for GL840 only): Pt100, JPt100, Pt1000

**Humidity** 0 to 100%RH - using optional sensor (B-530)


**Pulse** 4 channels\*  
Accumulating, Instant or RPM

**Logic** 4 channels\*

\* Requires optional input/output cable (B-513).  
Select either Pulse or Logic input.

### Large easy-to-read 7-inch wide color LCD(4.3-inch in the GL240)

Carries a clear 7-inch wide TFT color LCD screen (WVGA: 800 x 480 dots) for the GL840, and 4.3-inch wide LCD screen (WQVGA: 480 x 272 dots) for the GL240. Monitoring data are displayed in waveform or digital form option. Parameter settings can be displayed on the screen.




Waveform display (Analog + Digital)



Digital display



Dual display (Current + Past)



Waveform display (Analog only)

### Useful functions

#### Alarm output function

Based on set conditions for each channels, alarm signals can be placed using the four channel alarm output ports.\*

\* Input/output cable (B-513 option) is required to connect the alarm output ports to external buzzer/light mechanism.

#### USB drive mode

USB drive mode function enables data to be transferred to the PC from GL840/GL240 by drag & drop feature.

#### Navigation function

Simple to use navigation screen allows setting operation for measurement and wireless LAN adapter.

### Maximum sampling interval of up to 10ms

Provides faster sampling rates for voltage measurements. You are able to achieve up to 10ms sampling speed when limiting the number of channels in use.

| Model | Sampling interval |             | 10ms | 20ms | 50ms | 100ms | 200ms     | 500ms     | 1s        | 2s        |
|-------|-------------------|-------------|------|------|------|-------|-----------|-----------|-----------|-----------|
|       | Number of channel |             | 1    | 2    | 5    | 10    | 20        | 50        | 100       | 200       |
| GL840 | Measuring         | Voltage     | Yes  | Yes  | Yes  | Yes   | Yes       | Yes       | Yes       | Yes       |
|       |                   | Temperature | N/A  | N/A  | N/A  | Yes   | Yes       | Yes       | Yes       | Yes       |
| GL240 | Measuring         | Voltage     | Yes  | Yes  | Yes  | Yes   | Yes(10ch) | Yes(10ch) | Yes(10ch) | Yes(10ch) |
|       |                   | Temperature | N/A  | N/A  | N/A  | Yes   | Yes(10ch) | Yes(10ch) | Yes(10ch) | Yes(10ch) |

\* This chart is applicable when the captured data is saved in the GBD binary file format.

Limited sampling speed is available when digital sensors and GL100-WL are used as a remote monitoring device.

### Supports large-size SD memory card for reliable long term measurement

New GL series carries two SD memory card slots for storage device. The SDHC type SD memory card is supported up to 32GB. 4GB SD memory card comes as a standard accessory installed in the first slot.

Capturing time\* (When all 20 or 10 analog channels are being used with Logic/Pulse inputs turned off.)

| Model        | Sampling   | 10ms    | 50ms    | 100ms    | 200ms    | 500ms    | 1s       | 10s      |
|--------------|------------|---------|---------|----------|----------|----------|----------|----------|
| GL840 (20ch) | GBD format | 31 days | 77 days | 95 days  | 108 days | 270 days | over 365 | over 365 |
|              | CSV format | 3 days  | 11 days | 16 days  | 21 days  | 54 days  | 109 days | over 365 |
| GL240 (10ch) | GBD format | 41 days | 88 days | 103 days | 207 days | over 365 | over 365 | over 365 |
|              | CSV format | 3 days  | 11 days | 16 days  | 36 days  | 91 days  | 182 days | 365 days |

\* Figures are approximate. File size of captured data is 2GB in GBD or CSV file format on this chart. Sampling interval is limited by the number of channels in use. (10ms: 1ch, 50ms: 5ch, 100ms: 10ch) Limited sampling speed is available when digital sensors and GL100-WL are used as a remote monitoring device.

#### Ring capture function

The most recent data is saved when the memory is configured in ring memory mode. (Number of capturing data is 1000 to 2000000 points)

#### Relay capture function

Data is continuously saved to multiple files up to 2GB without losing any data until capturing is stopped when the memory is configured in the relay mode.

#### Hot-swapping the SD memory card

SD card can be replaced during data capturing when the sampling interval is 100ms or slower.

#### 3 Types of Power Source

Choose from AC power supply, DC supply\* or the rechargeable battery pack.\*

\* DC power drive cable (B-514) and battery pack (B-569) are optional accessories.

#### Networking features

##### Web & FTP server function

GL840/GL240 can be controlled externally via a network on the WEB browser, which also supports monitoring and transfer of signals and captured data.

##### FTP client function

Captured data is periodically transferred to the FTP server for backup.

##### NTP client function

The clock on the GL840/GL240 is periodically synchronized with the NTP server.

\* The GL840/GL240 needs to be connected to a LAN environment using the available Ethernet/WLAN ports.


# GL840 expands to two models for application specific use

## Multi-Input Model midi LOGGER GL840-M



Suitable for temperature measurement with multiple channels.

## High Voltage Withstand Model midi LOGGER GL840-WV



Suitable for stacked high voltage battery application, or high-precision temperature measurement.

## Expandable up to 200 channels



Standard configuration has 20 analog input channels. It is expandable to 200 channels by adding the optional 20 channel extension terminal base unit (B-566) and input terminal units (B-564 or B-565).

The following shows how a standard configuration is expanded to a 40 channel configuration.

1. Terminal unit is removed from the main body of the GL840.
2. Extension terminal base unit (B-566) connects to the GL840 using the external cable (B-567).



3. Terminal unit snaps onto the extension terminal base unit (B-566).
4. The combined extension terminal base set (B-566) and additional input terminals (B-564 or -565) are daisy chained together.



### Configuration for additional channels

| Number of channels                 | 20 channels | 40 channels | 100 channels | 200 channels |
|------------------------------------|-------------|-------------|--------------|--------------|
| GL840 unit (GL840-M or GL840-WV)   | 1 set       | 1 set       | 1 set        | 1 set        |
| Connection cable (B-567-05 or -20) | N/A         | 1 pc        | 1 pc         | 1 pc         |
| Terminal base (B-566)              | N/A         | 2 sets      | 5 sets       | 10 sets      |
| Input terminal (B-564 or B-565)    | N/A         | 1 set       | 4 sets       | 9 sets       |


\* Input terminal blocks for the B-564 and B-565 can be mixed together for combined configurations. However, the maximum voltage and accuracy rating for the setup will be limited to the rating of the B-564.

### Offers longer cable for the input terminals

Input terminal blocks can be connected directly (in daisy chain), or using the B-565 cable(s). This allows the input terminals to be placed in separate locations according to the need of the application.

The input terminal and the GL840 main body can be extended by using an extended connection cable.

\* If the signal is affected by noise, it may be required to use a slower sampling.




| Withstand voltage & Accuracy |                                 | Multi-input type (B-564)                      | Withstand-voltage type (B-565) |
|------------------------------|---------------------------------|---|--------------------------------|
| Voltage                      | Input voltage range             | 20 mV to 100 V                                | 20 mV to 100 V                 |
|                              | Max. voltage (Input - GND)      | 60 Vp-p                                       | 300 Vp-p                       |
| Temp.                        | Thermocouple                    | R, S, B, K, E, T, J, N, W (WRe5-26)           |                                |
|                              | RTD (Resistance Temp. Detector) | Pt100 (IEC751), JPt100 (JIS), Pt1000 (IEC751) |                                |
| Accuracy                     | Voltage                         | ± 0.1% of F.S.                                | ±(0.05% of FS + 10μV)          |
|                              | Temperature*                    | ± 1.55 °C                                     | ± 1.1 °C                       |

\* Accuracy rating for K-type thermocouple at 100°C includes reference junction compensation. Accuracy varies by the temperature levels and thermocouple types.

## Three types of input systems enable measurement of various signals

Along with the basic analog signal, Logic/Pulse, and digital sensors can be all connected to monitor a variety of measurements.



## Support digital sensors

Digital sensors and input terminal/adapters for the GL100 connects to the GL840 directly.

| Temp/Humidity GS-TH        | Acceleration/Temp GS-3AT | Carbon Dioxide GS-CO2                | Illuminance/UV GS-LXUV | Voltage/Temp GS-4VT |
|----------------------------|--------------------------|--------------------------------------|------------------------|---------------------|
|                            |                          |                                      |                        |                     |
| Thermistor adapter GS-4TSR | Thermistor               | AC current sensor adapter GS-DPA-AC* | AC current sensor      | Extension cable**   |
|                            |                          |                                      |                        |                     |

\* Supports up to two AC current sensors.  
\*\* Allows only one extension cable per port.

### Dual port adapter connects up to two sensors for simultaneous interface



## High performance software with useful functions for the PC (GL100\_240\_840-APS)

### Supports GL840, GL240, GL100

Up to 10 units of GL840, GL240 and GL100 can be connected to 1 PC simultaneously. Up to 1000 channels are supported.

### Controls settings for GL840, GL240, GL100

### Various measurement screen

Displays data in Y-T waveform, digital monitoring, statistical calculation result. The direct-Excel function enables captured data to be written directly to an Excel file.

### File operation

Data captured in multiple files can be merged into a single file. Using the *combine* function, data can be imported as a new channel overlaying on top of each other. The *bind* function connects the data in a time axis. When using the relay capture mode, the bind feature will append multiple files together into one large, continuous file.

### Useful functions

#### Scheduling function

Create a schedule for your monitoring to start and stop at selected time, and set an automatic measurement schedule.

#### Group function

Multiple units can be managed, such as controlling start or stop simultaneously. Data captured by each unit is saved in a single file.

### Data format conversion

Converts the GBD (Graphtec Binary Data) format to CSV format. The file size is reduced using the compression function saving a value at particular time point of a specified interval. Or, it will save the average, maximum, or minimum values from the specified time interval as the highlighted values.




Ethernet or USB



PC (Software)



Schedule table is able to create easily using mouse.



Multiple units

| Main unit series specifications                              |  |   |
|--|--|---|
| Item   | Description  |   |
| Model number   | GL840-M/GL840-WV   | GL240   |
| Number of analog input channels                              | 20 channels in standard configuration, Expandable up to 200 channels   | 10 channels   |
| Number of analog input terminals                             | Up to 10 terminals (standard config: 1)  | N/A   |
| Type of analog input terminal                                | Multi-input type, Withstand-voltage type   | N/A   |
| Port for digital sensor                                      | 1 port for the sensor/terminal of the GL100  | N/A   |
| External input/output *1                                     | Input *2: Trigger or Sampling (1 channel), Logic/Pulse (4 channels)<br>Output *3: Alarm (4 channels)   |   |
| Sampling interval  | 10 ms to 1 hour (10ms to 50ms: voltage only) *4, External signal   |   |
| Time scale of waveform display                               | 1 sec. to 24 hour /division  |   |
| Trigger, Alarm function                                      | Trigger action: Start or stop capturing data by the trigger<br>Repeat action: Off, On (auto rearmed)<br>Trigger source: Start: Off, Measured signal, Alarm, External, Clock, Week or Time<br>Stop: Off, Measured signal, Alarm, External, Clock, Week or Time      |   |
| Condition Setting  | Combination: OR or AND<br>Analog signal: Rising (High), Falling (Low), Window-in, Window-out<br>Logic signal: Pattern (combination of each input signal in high or low)<br>Pulse (number of count): Rising (High), Falling (Low), Window-in, Window-out            |   |
|  | Alarm output: Outputs a signal when alarm condition occurs in the input signal *5  |   |
|  | Rotation count (RPM) mode: Counts the number of pulses per sampling interval and converts to rpm (rotations per minute). Number of pulses for one rotation can be set to 50, 500, 5000, 50k, 500k, 5M, 50M, 500M rpm/F.S. (rpm./Full Scale)                        |   |
| Pulse input function   | Accumulating count mode: Accumulates the number of pulses from the start of measurement 50, 500, 5000, 50k, 500k, 5M, 50M, 500M C/F.S. (Counts/Full Scale)   |   |
|  | Instant count mode: Counts the number of pulses per sampling interval 50, 500, 5000, 50k, 500k, 5M, 50M, 500M C/F.S. (Counts/Full Scale)   |   |
| Calculation function   | Between channels: Addition, Subtraction, Multiplication, and Division for analog input<br>Statistical: Select two calculations from Average, Peak, Maximum, Minimum, RMS   |   |
|  | Search function: Search for analog signal levels, values of logic or pulse or alarm point in captured data   |   |
| Interface to PC  | Ethernet, USB 2.0 (Hi-speed), USB 2.0 (Hi-speed)   |   |
| Storage device   | Media  | SD memory card (Support SDHC, up to 32 GB), supports 2 slots *6                     |
|  | Saved contents   | Captured data, Setting conditions, Screen copy                                      |
| Capturing mode   | Mode: Normal, Ring, Relay<br>Ring: Saves most recent data (Number of capturing data: 1000 to 2000000 points) *7<br>Relay: Saves data to multiple files without losing data until data capturing is stopped.  |   |
| Replay data (in GBD or CSV format)                           | Replays captured data that was saved in the GL840  | Replays captured data that was saved in the GL240                                   |
| Scaling (Engineering unit) function                          | Measured value can be converted to specified engineering unit<br>• Analog voltage: Converts using four reference points (gain, offset)<br>• Temperature: Converts using two reference points (offset)<br>• Pulse count: Converts using two reference points (gain) |   |
| Action during data capture                                   | • Displaying past data (using dual display mode (Current + Past data))<br>• Hot-swapping the SD memory card<br>• Saving data in between cursors  |   |
| Display (LCD)  | Size   | 7-inch color TFT (WVGA: 800 x 480 dots), 4.3-inch color TFT (WQVGA: 480 x 272 dots) |
|  | Language   | English, French, German, Chinese, Korean, Russian, Spanish, Japanese                |
| Information *8   | Waveform in Y-T with digital values, Waveform only, Digital value, Digital values and statistics values  |   |
| Operating environment  | 0 to 45 °C, 5 to 85 % RH (non condensed)<br>(When operating with battery pack 0 to 40 °C, charging battery 15 to 35 °C)  |   |
| Power source   | AC adapter   | 100 to 240 V AC, 50/60 Hz (1 pc of adapter is attached as standard accessory)       |
|  | DC power   | 8.5 to 24 V DC (DC drive cable (option B-514) is required)                          |
|  | Battery pack   | Mountable battery pack (battery pack (option B-517): 7.2V DC, 2900mAh)              |
| Power consumption *9   | Max. 38 VA   | Max. 36 VA  |
| External dimensions (W x D x H in mm, Excluding projections) | GL840-M: Approx. 240 x 158 x 52.5<br>GL840-WV: Approx. 240 x 166 x 52.5  | Approx. 188 x 117 x 42  |
| Weight *10   | GL840-M: Approx. 1010 g<br>GL840-WV: Approx. 1035 g  | Approx. 500 g   |

### Software specifications for PC

| Item                       | Description  |
|----------------------------|--|
| Model name                 | GL100_240_840-APS  |
| Supported OS               | Windows 8.1, 8, 7, Vista (32/64-bit edition)   |
| Supported device           | GL840 (USB, Ethernet), GL240 (USB), GL100 (USB)  |
| Functions                  | Control the GL series, Real-time data capture, Replay data, and Data format conversion   |
| Supported units & channels | Up to 1000 channels total, Up to 4 groups (number of units is limited by model)  |
| Settings control           | Input condition, Capturing condition, Trigger/Alarm condition, Report, etc.  |
| Capturing data             | Saved to PC: Saves captured data in real time (in GBD binary or CSV format)  |
|                            | Saved to GL unit: Saves to the SD memory card (in GBD binary or CSV format)  |
| Displayed information      | Y-T waveform, Digital values, Report, X-Y graph (specified period of data, data reply only), Two display for the current and past, and Statistical calculation |
| File operation             | Converting data format to CSV from GBD binary, merge multiple data files in the time axis or as an additional channel  |
| Warning function           | Send e-mail to the specified address when the alarms occur   |
| Statistical calculation    | Maximum, Minimum, and Average during data capturing  |
| Report function            | Creates the daily or monthly report automatically  |

- Input/Output cable for GL (option B-513) is required to connect the signal.
- Input signal: • Voltage range: up to 24V (common ground) • Signal type: Voltage, Open collector, Contact (relay)  
• Threshold: approx +2.5 V (Hysteresis: approx 0.5V (2.5V to 3V))
- Output signal: Open collector (pull-up to 5V by 10kΩ resistor)  
• Maximum rating of the output transistor:  
Voltage: 30V, Current: 0.5A, Collector dissipation: 0.2W
- Minimum interval varies by number of channels used.
- Output port can be specified in each input channel.
- 4GB SD memory card is installed to slot 1 as standard accessory.
- Size of the capture data will be limited to 1/3 available memory.
- Display mode is switched every time the dedicated key is pressed. In magnified digital value mode, the displayed channel number can be specified. In the waveform display mode, the changing of the time scale will be effective from the point of the next displayed data.
- Rating under maximum power consumption using the AC adapter, with LCD display on, and battery pack(s) being charged.
- Excludes AC adapter and battery pack.
- The terminal "b" for using the RTD is connected each other across all channels.
- If the specifications of the temperature sensor is lesser or greater than the selected measurement range, GL840 can measure up to the specifications of the sensor.
- Subject to the following conditions:  
• Room temperature is 23 °C ± 5 °C.  
• When 30 minutes or more have elapsed after power was turned on.  
• Filter is set to 10.  
• Sampling rate is set to 1 sec, using 20-channel in GL840-M, 10-channel in GL840-WV and 10-channel in GL240.  
• GND terminal is connected to ground.
- Wire size of thermocouple used is 0.32mm diameter in the T type and 0.65mm diameter in other types.  
• The "TS" is the "Temperature Sensed".
- Supports 3-wire type sensor.

| Analog input specifications    |  |   |   |                            |
|--------------------------------|--|---|---|----------------------------|
| Item                           | Description  |   |   |                            |
| Model number                   | GL840 series   |   |   |                            |
| Input method                   | All channels isolated balanced input *11, Scans channels for sampling, Screw terminal (M3) |   |   |                            |
| Measurement range              | Voltage  | 20, 50, 100, 200, 500 mV, 1, 2, 5, 10, 20, 50, 100 V, and 1-5V F.S. (Full Scale)      |   |                            |
|                                | Thermocouple   | Type: K, J, E, T, R, S, B, N, W (WRRe5-26), Range: 100, 500, 2000 °C *12              | Type: K, J, E, T, R, S, B, N, W (WRRe5-26)                |                            |
|                                | RTD (Resistance Temperature Detector)  | Type: Pt100, JPt100 (JIS), and Pt1000 (IEC751) Range: 100, 500, 2000 °C *12           | N/A   |                            |
|                                | Humidity   | 0 to 100 % RH - using the humidity sensor (option B-530)                              |   |                            |
| Filter                         | Off, 2, 5, 10, 20, 40 (moving average in selected number)                                  |   |   |                            |
| Measurement accuracy *13       |  |   |   |                            |
| Model number                   | GL840-M, Input terminal B-564  | GL840-WV, Input terminal B-565  | GL240   |                            |
| Voltage                        | ± 0.1% of F.S. (Full Scale)  | ± (0.05% of F.S. + 10μV)  | ± 0.1% of F.S. (Full Scale)                               |                            |
| Temperature (Thermocouple) *14 |  |   |   |                            |
| Type                           | Measurement range *15  | Measurement accuracy  | Measurement accuracy                                      |                            |
| R/S                            | 0 ≤ TS ≤ 100 °C  | ± 5.2 °C  | ± 4.5 °C  |                            |
|                                | 100 < TS ≤ 300 °C  | ± 3.0 °C  | ± 3.0 °C  |                            |
|                                | R: 300 < TS ≤ 1600 °C<br>S: 300 < TS ≤ 1760 °C   | ± (0.05% of rdg. + 2.0 °C)  | ± 2.2 °C  | ± (0.05% of rdg. + 2.0 °C) |
| B                              | 400 ≤ TS ≤ 600 °C  | ± 3.5 °C  | ± 3.5 °C  |                            |
|                                | 600 < TS ≤ 1820 °C   | ± (0.05% of rdg. + 2.0 °C)  | ± 2.5 °C  | ± (0.05% of rdg. + 2.0 °C) |
| K                              | -200 ≤ TS ≤ -100 °C  | ± (0.05% of rdg. + 2.0 °C)  | ± 1.5 °C  | ± (0.05% of rdg. + 2.0 °C) |
|                                | -100 < TS ≤ 1370 °C  | ± (0.05% of rdg. + 1.0 °C)  | ± 0.8 °C  | ± (0.05% of rdg. + 1.0 °C) |
| E                              | -200 ≤ TS ≤ -100 °C  | ± (0.05% of rdg. + 2.0 °C)  | ± 1.0 °C  | ± (0.05% of rdg. + 2.0 °C) |
|                                | -100 < TS ≤ 800 °C   | ± (0.05% of rdg. + 1.0 °C)  | ± 0.8 °C  | ± (0.05% of rdg. + 1.0 °C) |
| T                              | -200 ≤ TS ≤ -100 °C  | ± (0.1% of rdg. + 1.5 °C)   | ± 1.5 °C  | ± (0.1% of rdg. + 1.5 °C)  |
|                                | -100 < TS ≤ 100 °C   | ± (0.1% of rdg. + 0.5 °C)   | ± 0.6 °C  | ± (0.1% of rdg. + 0.5 °C)  |
| J                              | -200 ≤ TS ≤ -100 °C  | ± 2.7 °C  | ± 1.0 °C  | ± 2.7 °C                   |
|                                | -100 < TS ≤ 100 °C   | ± 1.7 °C  | ± 0.8 °C  | ± 1.7 °C                   |
| N                              | 100 < TS ≤ 1100 °C   | ± (0.05% of rdg. + 1.0 °C)  | ± 0.6 °C  | ± (0.05% of rdg. + 1.0 °C) |
|                                | -200 ≤ TS < 0 °C   | ± (0.1% of rdg. + 2.0 °C)   | ± 2.2 °C  | ± (0.1% of rdg. + 2.0 °C)  |
| W                              | 0 ≤ TS ≤ 1300 °C   | ± (0.1% of rdg. + 1.0 °C)   | ± 1.0 °C  | ± (0.1% of rdg. + 1.0 °C)  |
|                                | 0 ≤ TS ≤ 2000 °C   | ± (0.1% of rdg. + 1.5 °C)   | ± 1.8 °C  | ± (0.1% of rdg. + 1.5 °C)  |
| R.J.C.                         | ± 0.5 °C   | ± 0.3 °C  | ± 0.5 °C  |                            |
| Temperature (RTD) *16          |  |   |   |                            |
| Type                           | Measurement range *15  | Measurement accuracy  | Measurement accuracy                                      |                            |
| Pt100                          | -200 ≤ TS ≤ 100 °C   | ± 1.0 °C  | ± 0.6 °C  |                            |
|                                | 100 < TS ≤ 500 °C  |   | ± 0.8 °C  |                            |
|                                | 500 < TS ≤ 850 °C  |   | ± 1.0 °C  |                            |
| JpT100                         | -200 ≤ TS ≤ 100 °C   | ± 0.8 °C  | ± 0.6 °C  |                            |
|                                | 100 < TS ≤ 500 °C  |   | ± 0.8 °C  |                            |
| Pt1000                         | -200 ≤ TS ≤ 100 °C   | ± 0.8 °C  | ± 0.6 °C  |                            |
|                                | 100 < TS ≤ 500 °C  |   | ± 0.8 °C  |                            |
| A/D converter                  |  |   |   |                            |
| Maximum input voltage          | Between (+) / (-)  | Sigma-Delta type, 16 bits (effective resolution: 1/40000 of the measuring full range) |   |                            |
| Channels (-) / (+)             | 20 mV to 2 V range: 60 Vp-p, 5 V to 100 V range: 110 Vp-p                                  |   | 20 mV to 1 V range: 60 Vp-p, 2 V to 100 V range: 110 Vp-p |                            |
|                                | 60 Vp-p  | 600 Vp-p  | 60 Vp-p   |                            |
|                                | 60 Vp-p  | 300 Vp-p  | 60 Vp-p   |                            |
| Max. voltage (withstand)       | Between channels   | 350 Vp-p (1 minute)   | 600 Vp-p (1 minute)                                       |                            |
|                                | Channel / GND  | 350 Vp-p (1 minute)   | 2300 Vrms AC (1 minute)                                   |                            |

### Options and Accessories

| Item                                      | Model number | Description   |
|---|--------------|---|
| Input terminal (Multi-input)              | B-564        | 20ch input terminal, multi-input type, for GL840                      |
| Input terminal (Withstand voltage)        | B-565        | 20ch input terminal, withstand-high-voltage type, for GL840           |
| Base unit for input terminal              | B-566        | Base unit for input terminal (B-564 or 565), for GL840                |
| Connection cable for extension terminal   | B-567-05     | Cable to connect GL840 and B-566, 50 cm long                          |
| Battery pack                              | B-567-20     | Cable to connect GL840 and B-566, 2 m long                            |
| Bracket for DIN rail (GL840 main body)    | B-569        | Rechargeable Lithium-ion battery (7.2 V, 2900mAh)                     |
| Bracket for DIN rail (extension terminal) | B-570        | Bracket for DIN rail (GL840 main body), for GL840, Build-to-order     |
| Input/Output cable for GL series          | B-540        | Bracket for DIN rail (B-566 terminal base), for GL840, Build-to-order |
| DC drive cable                            | B-513        | 2 m long (no clip on end of cable)                                    |
| Humidity sensor                           | B-514        | 2 m long (no clip on end of cable)                                    |
| Shunt resistor                            | B-510        | With 3 m long signal cable (with power plug)                          |
| AC power adapter                          | B-551-10     | 250 ohms (it converts the signal to the "1-5V" from the "4-20mA")     |
| Temp & Humidity sensor                    | ACADP-20     | Input: 100 to 240 V AC, Output: 24 V DC                               |
| Illuminance & UV sensor                   | GS-TH        | Temperature and humidity measurement, for GL840                       |
| Carbon Dioxide (CO2) sensor               | GS-LXUV      | Illuminance and UV measurement, cable 20cm long, for GL840            |
| Acceleration & Temp sensor                | GS-CO2       | CO2 measurement, cable 20cm long, for GL840                           |
| Thermistor input terminal                 | GS-3AT       | Acceleration and temp. measurement, cable 20cm long, for GL840        |
| Thermistor sensor (Normal type)           | GS-4TSR      | Temp measurement (using a Thermistor), cable 20cm long, for GL840     |
| Thermistor sensor (Ulathrin type)         | GS-103AT-4P  | Temperature sensor (-40 to 105 °C), 3m long, 4pcs/set, for GS-4TSR    |
| AC current sensor adapter                 | GS-103JT-4P  | Temperature sensor (-40 to 120 °C), 3m long, 4pcs/set, for GS-4TSR    |
| AC current sensor (50A)                   | GS-DPA-AC    | Current measurement (using a CT), cable 20cm long, for GL840          |
| AC current sensor (100A)                  | GS-AC50A     | Current sensor (CT) 50A, cable 20cm long, for GS-DPA-AC               |
| AC current sensor (200A)                  | GS-AC100A    | Current sensor (CT) 100A, cable 20cm long, for GS-DPA-AC              |
| Voltage & Temp input terminal             | GS-AC200A    | Current sensor (CT) 200A, cable 20cm long, for GS-DPA-AC              |
| Module extension cable                    | GS-4VT       | Voltage or Temp (using a thermocouple), cable 20cm long, for GL840    |
| Dual port adapter                         | GS-EXC       | Extension cable for the sensor/terminal, 1.5m long, for GL840         |
|   | GS-DPA       | Connect up to 2 sensor modules, for GL840                             |

- Due to the possibility of equipment or PC failure, the data files on the instrument will not be guaranteed to be held on the memory. Please make a backup of data whenever possible to avoid data loss.
- Brand names and product names listed in this brochure are the trademarks or registered trademarks of their respective owners.
- Specifications are subject to change without notice. For more information about product, please check the web site or contact your local representative.

 For using equipment in correctly and safely

Before using it, please read the user manual and then please use it properly in accordance with the description.  
To avoid malfunction or an electric shock by current leakage or voltage, please ensure a ground connection and use according to the specification.

# GRAPHTEC

Graphtec Corporation

503-10 Shinano-cho, Totsuka-ku, Yokohama 244-8503, Japan  
Tel : +81-45-825-6250 Fax : +81-45-825-6396  
Email : webinfo@graphtec.co.jp

Website <http://www.graphteccorp.com>



KE10045 GR Vol.1